



## essential range

### Features and Benefits

- Clean, uncluttered profile for a modern, streamlined look
- Rounded box section interlocks and mullions prevent curtains from being damaged by sharp edges
- Euro track roller system ensures smooth sliding action
- Handle has mortice lock for superior security
- Improved key positioning for easier operation
- Integrated tracks for insect, safety and **Stainless View™** screens

### Performance Parameters

<b>Maximum door height</b>	2450mm
<b>Maximum door width</b>	6246mm
<b>Maximum panel width</b>	1350mm
<b>Maximum panel weight</b>	50kg
<b>Maximum water rating</b>	300pa
<b>Maximum wind rating</b>	N4 (as per AS4055 – Wind loads for housing)
<b>Maximum glass thickness</b>	6.76mm
<b>Maximum acoustic rating</b>	Rw30

Endless possibilities across the range...



## signature range

### Features and Benefits

- Multi-track system allows for flexibility in design and application
- Available in 90° and 135° corner configurations (without a post)
- Available in multiple 'cavity' configurations
- Rounded box section interlocks and mullions prevent curtains from being damaged by sharp edges
- Euro track roller system ensures smooth sliding action
- Wider glazing pockets for superior acoustic and thermal performance
- Handle has mortice lock for superior security
- Improved key positioning for easier operation
- Integrated tracks for insect, safety and **Stainless View™** screens

### Performance Parameters

<b>Maximum door height</b>	2700mm
<b>Maximum door width</b>	6246mm
<b>Maximum panel width</b>	1350mm
<b>Maximum panel weight</b>	100kg
<b>Maximum water rating</b>	Standard sill = 360pa High performance sill = 600pa*
<b>Maximum wind rating</b>	N6 (as per AS4055 – Wind loads for housing)
<b>Maximum glass thickness</b>	12.76mm (single glazed) 20mm (IGUs)
<b>Maximum acoustic rating</b>	Rw35

*\*Does not apply to 166mm frame*



## commercial range

### Features and Benefits

- Multi-track system allows for flexibility in design and application
- Available in 90° and 135° corner configurations (without a post)
- Available in multiple 'cavity' configurations
- Rounded box section interlocks and mullions prevent curtains from being damaged by sharp edges
- Multiple bogey roller options for smooth sliding action
- Wider glazing pockets for superior acoustic and thermal performance
- Handle has mortice lock for superior security
- Improved key positioning for easier operation
- Integrated tracks for insect, safety and **Stainless View™** screens

### Performance Parameters

<b>Maximum door height</b>	3100mm
<b>Maximum door width</b>	12000mm
<b>Maximum panel width</b>	1800mm
<b>Maximum panel weight</b>	160kg
<b>Maximum water rating</b>	Standard sill = 415pa High performance sill = 650pa
<b>Maximum wind rating</b>	N6 (as per AS4055 – Wind loads for housing)
<b>Maximum glass thickness</b>	10.76mm (single glazed) 28mm (IGUs)
<b>Maximum acoustic rating</b>	Rw34



Say goodbye  
to convention...

## cavity sliding doors

signature | commercial

### A fusion of ingenuity and practicality

Bradnam's **Cavity Doors** will revolutionise how outdoor and entertainment areas are designed. Unlike traditional 'entertainment doors' such as stacker doors or bi-fold doors, our Cavity Doors truly provide unobstructed views and access. Seamlessly gliding out of sight, they don't have fixed or folded panels blocking the view or access from the inside to the outside.

